



SAFETY DATA SHEET

Kraftrens

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Kraftrens

Product no.

224

Unique formula identifier (UFI)

3A10-V2P7-0001-GJ12

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Alkaline cleaner.

Use descriptors (UK REACH)

Sectors of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC 35	Washing and Cleaning Products (including solvent based products)
Process category	Description
PROC 28	Manual maintenance (cleaning and repair) of machinery
PROC 19	Hand-mixing with intimate contact and only PPE available
PROC 8a	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems
ERC 8b	Wide dispersive indoor use of reactive substances in open systems

EuPCS

PC-CLN-13.1 / Floor cleaning products

PC-CLN / Cleaning, care and maintenance products (excludes biocidal products)

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Jysk Kemi Service A/S

Gl. Struervej 50

7500 Holstebro

Denmark

+45 9740 3133

+45 9740 4846

www.jyskkemi.dk

Contact person

Rikke Hunsbjerg

E-mail

rikke@jyskkemi.dk

Revision

16/05/2024

SDS Version

5.0

Date of previous version

05/10/2023 (4.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Skin Corr. 1B; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Causes severe skin burns and eye damage. (H314)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Do not breathe vapour/mist. (P260)

Wear eye protection/face protection/protective gloves. (P280)

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. (P303+P361+P353)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. (P305+P351+P338)

Storage

-

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

sodium hydroxide

Sodium Laureth sulfate

fedtalkoholalkoxylat

Additional labelling

UFI: 3A10-V2P7-0001-GJ12

▼ Labelling of contents according to Detergents Regulation (EC) No 648/2004 as retained and amended in UK law

5% - 15%

· Amphoteric surfactants

< 5%

· Anionic surfactants

· Non-ionic surfactants

2.3. Other hazards

▼ Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.:	3-5%	Eye Irrit. 2, H319	[1], [3]
sodium hydroxide	CAS No.: 1310-73-2 EC No.: 215-185-5 UK-REACH: Index No.: 011-002-00-6	1-3%	Skin Corr. 1A, H314 Skin Corr. 1B, H314 (SCL: 2.00 %) Skin Irrit. 2, H315 (SCL: 0.50 %) Eye Irrit. 2, H319 (SCL: 0.50 %)	
Sodium Laureth sulfate	CAS No.: 68891-38-3 EC No.: 500-234-8 UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Eye Dam. 1, H318 (SCL: 10.00 %) Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 3, H412	[19]
fedtalkoholalkoxylat	CAS No.: 111905-52-3 EC No.: UK-REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Eye Dam. 1, H318	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

▼ Skin contact

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal



contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Not applicable.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: 2X

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage temperature

> 0°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 101,2

sodium hydroxide

Short term exposure limit (15 minutes) (mg/m³): 2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

2-(2-butoxyethoxy)ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	10 mg/kg kropsvægt/dag
Long term – Systemic effects - Workers	Dermal	20 mg/kg kropsvægt/dag
Long term – Local effects - General population	Inhalation	5 mg/m ³
Long term – Local effects - Workers	Inhalation	67.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	5 mg/kg kropsvægt/dag
Long term – Systemic effects - Workers	Inhalation	10 ppm
Short term – Local effects - General population	Inhalation	7,5 mg/m ³
Short term – Local effects - Workers	Inhalation	14 ppm
Short term – Local effects - Workers	Inhalation	101.2 mg/m ³
Long term – Systemic effects - General population	Oral	1,3 mg/kg kropsvægt/dag
Long term – Systemic effects - General population	Oral	6.25 mg/kg bw/day

sodium hydroxide

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	1 mg/m ³
Long term – Local effects - Workers	Inhalation	1 mg/m ³
Short term – Local effects - Workers	Inhalation	1 mg/m ³

Sodium Laureth sulfate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	79 µg/cm ²
Long term – Local effects - Workers	Dermal	132 µg/cm ²
Long term – Systemic effects - General population	Dermal	1650 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	2750 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	52 mg/m ³
Long term – Systemic effects - Workers	Inhalation	175 mg/m ³
Long term – Systemic effects - General population	Oral	15 mg/kg bw/day

PNEC

2-(2-butoxyethoxy)ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg
Intermittent release (freshwater)		11 mg/L
Marine water		110 µg/L
Marine water sediment		440 µg/kg
Predators		56 mg/kg
Soil		0,4 mg/l
Soil		320 µg/kg

Sodium Laureth sulfate		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		240 µg/L
Freshwater sediment		916.8 µg/kg
Intermittent release (freshwater)		71 µg/L
Marine water		24 µg/L
Marine water sediment		91.7 µg/kg
Sewage treatment plant		10 g/L
Soil		7.5 mg/kg

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

▼ Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Combination filter A2P2	Class 2	Brown/White	EN14387



Skin protection

Recommended	Type/Category	Standards
No special when used as intended	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Neoprene - Discard immediately after use	0.6	> 240	EN374-2, EN374-3, EN388



Eye protection

Type	Standards

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Clear

Odour / Odour threshold

Characteristic

pH

13,5

 Density (g/cm³)

1.06

Kinematic viscosity

No data available

Particle characteristics

Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)

Not applicable - product is a liquid

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

100

Vapour pressure

No data available

Relative vapour density

No data available

Decomposition temperature (°C)

Not applicable

Data on fire and explosion hazards

Flash point (°C)

No data available

Flammability (°C)

No data available

Auto-ignition temperature (°C)

No data available

Lower and upper explosion limit (% v/v)

No data available

Solubility

Solubility in water

Completely soluble

 n-octanol/water coefficient (LogK_{ow})

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Sensitivity to shock

No

Evaporation rate (n-butylacetate = 100)

No data available

Oxidizing properties

Not applicable

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Thermal decomposition may produce corrosive vapours.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law****Acute toxicity**

Product/substance	2-(2-butoxyethoxy)ethanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (2 hours)
Result:	> 29 ppm

Product/substance	2-(2-butoxyethoxy)ethanol
Test method:	OECD 402
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	2764 mg/kg

Product/substance	2-(2-butoxyethoxy)ethanol
Test method:	OECD 401
Species:	Mouse
Route of exposure:	Oral
Result:	2410 mg/kg

Product/substance	sodium hydroxide
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	325 mg/kg ·

Product/substance	fedtalkoholalkoxylyat
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg ·

▼ Skin corrosion/irritation

Product/substance	2-(2-butoxyethoxy)ethanol
Test method:	OECD 404
Result:	No adverse effect observed (Not irritating)

Causes severe skin burns and eye damage.

▼ Serious eye damage/irritation

Product/substance 2-(2-butoxyethoxy)ethanol
Result: Adverse effect observed (Slightly irritating)

Causes serious eye damage.

▼ Respiratory sensitisation

Product/substance 2-(2-butoxyethoxy)ethanol
Result: No adverse effect observed (not sensitising)

▼ Skin sensitisation

Product/substance sodium hydroxide
Species: Rabbit
Description: Meget ætsende
Result: Adverse effect observed (sensitising)

▼ Germ cell mutagenicity

Product/substance 2-(2-butoxyethoxy)ethanol
Conclusion: No adverse effect observed

Carcinogenicity

Product/substance 2-(2-butoxyethoxy)ethanol
Conclusion: No adverse effect observed

Reproductive toxicity

Product/substance 2-(2-butoxyethoxy)ethanol
Conclusion: No adverse effect observed

STOT-single exposure

Product/substance 2-(2-butoxyethoxy)ethanol
Conclusion: No adverse effect observed

STOT-repeated exposure

Product/substance 2-(2-butoxyethoxy)ethanol
Conclusion: No adverse effect observed

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance 2-(2-butoxyethoxy)ethanol
Test method: OECD 203
Species: Fish, *Lepomis macrochirus*
Duration: 96 hours
Test: LC50
Result: 1300 mg/L

Product/substance 2-(2-butoxyethoxy)ethanol
Species: Algae, *Daphnia magna*
Duration: 48 hours
Test: EC50
Result: > 100 mg/L

Product/substance sodium hydroxide

Species:	Fish
Duration:	7 days
Test:	LC50
Result:	125 mg/l ·

Product/substance	sodium hydroxide
Species:	Daphnia
Duration:	24 hours
Test:	EC50
Result:	145 mg/l ·

Product/substance	sodium hydroxide
Species:	Crustacean
Duration:	15 min
Test:	EC50
Result:	22 mg/l ·

Product/substance	sodium hydroxide
Species:	Daphnia, Ceriodaphnia dubia
Duration:	48 hours
Test:	EC50
Result:	40,4 mg/L

Product/substance	fedtalkoholalkoxylat
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	1-10 mg/L

12.2. ▼ Persistence and degradability

Product/substance	2-(2-butoxyethoxy)ethanol
Result:	80-90%
Conclusion:	Readily biodegradable
Test:	OECD 301 C

Product/substance	fedtalkoholalkoxylat
Result:	> 60%
Conclusion:	Readily biodegradable
Test:	OECD 301 B

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents as retained and amended in UK law. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. ▼ Bioaccumulative potential

Product/substance	2-(2-butoxyethoxy)ethanol
Conclusion:	No potential for bioaccumulation

Product/substance	sodium hydroxide
Conclusion:	No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations



Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)
 HP 8 – Corrosive
 Dispose of contents/container to an approved waste disposal plant.
 Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code




20 01 15* Alkalines
 Waste group H Waste group H

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1760	CORROSIVE LIQUID, N.O.S. (sodium hydroxide)	Transport hazard class: 8 Label: 8 Classification code: C9 	II	No	Limited quantities: 1 L Tunnel restriction code: (E) See below for additional information.
IMDG	UN1760	CORROSIVE LIQUID, N.O.S. (sodium hydroxide)	Transport hazard class: 8 Label: 8 Classification code: C9 	II	No	Limited quantities: 1 L EmS: F-A S-B See below for additional information.
IATA	UN1760	CORROSIVE LIQUID, N.O.S. (sodium hydroxide)	Transport hazard class: 8 Label: 8 Classification code: C9 	II	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: 2X

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

UK-REACH, Annex XVII

2-(2-butoxyethoxy)ethanol is subject to restrictions, UK-REACH annex XVII (entry 55).

Labelling of contents according to Detergents Regulation (EC) No 648/2004 as retained and amended in UK law

5% - 15%

· Amphoteric surfactants

< 5%

· Anionic surfactants

· Non-ionic surfactants

Product registration number

4437139

Additional information

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents as retained and amended in UK law. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources

The Management of Health and Safety at Work Regulations 1999.

Regulation (EC) No 648/2004 on detergents as retained and amended in UK law.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H412, Harmful to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC 28 = Manual maintenance (cleaning and repair) of machinery

PROC 19 = Hand-mixing with intimate contact and only PPE available

PROC 8a = Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PC 35 = Washing and Cleaning Products (including solvent based products)

ERC 8a = Wide dispersive indoor use of processing aids in open systems

ERC 8b = Wide dispersive indoor use of reactive substances in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

▼ The safety data sheet is validated by

RH

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en