

TDS og instruction

Sprit IPA

Cleaner and thinner

Item number 908-000031 PR number 2496338



IPA (Isopropyl alcohol) alcohol 97-98% denatured alcohol.

Areas of application

For cleaning and degreasing before painting or coating, for lowering the freezing point in water by e.g. window cleaning and for cleaning painting tools that have been used for certain types of epoxy.

Thinning of certain types of paint materials.

Treatment

Concentrated or water-diluted alcohol is applied with a brush or cloth. Avoid application methods that create spray mist. The treated surface can advantageously be processed mechanically.

Limitations

Do not work with alcohol on hot surfaces. Harmful vapours will form. Avoid sparks and open flame. Highly flammable liquids and vapours.

Warning/Safety

Use gloves.

Avoid contact with skin, hair and eyes.

Use eye protection and respirator with filter A-P2.

Keep out of reach of children.

Transport

UN 1307 - ALCOHOLS, N.O.S. (Ethanol, propan-2-ol).

Transport hazard class 3 packaging group II

The mentioned information is based on laboratory experiments and practical testing at 20°C and 85% RH. If the temperature or humidity of the material, the substrate or the surroundings deviate from this, the product properties, drying and curing times are affected. A general responsibility for paint treatment cannot be given, due to the many caveats that may arise regarding the substrate, application method, etc. Where the consumption of a paint extend over more batches, these should be intermixed to avoid sheen and shade differences. It is the user's responsibility to always obtain new and revised product sheets. We reserve the right to make changes without notice. We reserve the right for printing errors. In case of inconsistency between language versions, the Danish version applies.

Type: Solvent

Areas of application:

Cleaning and dilution

Active substances:

Ethanol approx. 75%

Isopropyl alcohol approx. 25%

Butane approx. 1%

Density: Approx. 0.79 kg/l ISO 2811

Concentration: 97-98%

Boiling point: 73-81°C

Flash point: 17°C

Autoignition temperature: 365°C

Odours: Alcohol

Warning:

Avoid contact with strong alkali and acetic anhydride

Avoid heating and contact with sources of ignition

Application temperature:

Developed for use at 0°C-25°C (substrate and surroundings)

Cleaning tools:

Water

Storage:

Store at +0°C-+25°C, not in direct sunlight and inaccessible to children

Shelf life:

Min. 24 months from production date when stored correctly (Batch no. yymmdd)

Packaging: 20 litres

Colours: Clear

CLP symbols:



CLP signal word: Danger

MAL code: 3-1

Protective gear:



Document date: 20-11-2022



Promal A/S • Joachim Wellers Vej 27 • DK-7500 Holstebro
+45 9610 5080 • info@promal.dk • www.promal.dk