

This specification describes articles of the material group



PLA – polylactic acid



Material description

PLA is generated through the production of lactic acid from glucose from fermentation. In the second step a polymerization is added to the resulting lactic acid. The glucose is obtained by the grinding and subsequent saccharification from plants which contain starch.

PLA can be processed in similar plants as PE: injection moulding, deep-draw, sheet blowing. PLA consists of renewable raw materials, has a high stiffness factor, is moisture and grease resistant and has a high gloss. The material is transparent, printable, bio-degradable, food-save, but not heat resistant.

Product description

Picture	Description	Art.-No.	Calibration	Nominal capacity (dl)	Brim capacity (dl)	Diameter (mm)
	Cup for water dispenser	13308	-	1,5	1.65	70
	Cup for water dispenser	5013	-	2	2.10	70

Picture	Description	Art.-No.
	Sauce cups	10048, 10049, 10050
	Lid for sauce cups	10536

PRODUCT-SPECIFICATION_00714/e DECLARATION OF COMPLIANCE



Material / composition

PLA

Storage

Storage temperature: ambient
Relative humidity: dry
Storage conditions: keep away from direct sunlight

Purpose of use

Types of food to be in contact with the material:

all types of food

Applications:

- Temperature resistant up to 40°C
- Deep freezing -18°C
- Long-term storage at room temperature or below
- Single-use

NOT suitable applications:

- Oven
- Microwave

Declaration of compliance

These articles meet the following regulations and are suitable for direct contact with food :

- Regulation (EC) No 2023/2006** on good manufacturing practice for materials and articles intended to come into contact with food
- Regulation (EC) No 1935/2004** on materials and articles intended to come into contact with food and
- Regulation (EU) No 10/2011** on plastic materials and articles intended to come into contact with food. And subsequent amendments until 2019/1338
- SR 817.023.21** The Swiss Ordinance on Materials and Articles in Contact with Food
- Directive 94/62/EC** on packaging and packaging waste

page 2 / 4

PRODUCT-SPECIFICATION_00714/e DECLARATION OF COMPLIANCE



Overall migration

Tested under the following conditions (test report SQTS 2018L42608):

Simulant	Time	Temperature
<input checked="" type="checkbox"/> B: Acetic acid 3 % (v/v)	10 days	40°C
<input checked="" type="checkbox"/> D2: Vegetable oil	10 days	40°C
<input checked="" type="checkbox"/> Alternative simulant Ethanol 95 % (v/v)	10 days	40°C

The global migration values are below the limit of 10 mg/dm² and 60 mg/kg.

Specific migration

Compliance with the regulations cited above is based, on the one hand, on the information provided by our suppliers, who do not disclose all ingredients to us due to secrecy, and on the other hand on our own migration tests, which we commissioned in order to validate the plausibility. Based on both the subcontractor's documents and own results, compliance with the specific migration can be confirmed.

Calculation basis

Ratio of food contact surface area to volume used to establish the compliance of the material or article: 6 dm²/kg

Dual-use additives

The following dual-use additives may be included in the material:

Lactic Acid, CAS-No. 50-21-5, E270

Functional barriers

No functional barriers are used.

Sensory testing

The articles were examined sensory.

Under normal or foreseeable conditions of use, they do not affect the organoleptic properties of the food.

PRODUCT-SPECIFICATION_00714/e DECLARATION OF COMPLIANCE



Production location: Taiwan

Bio-degradability: The products are bio-degradable

Certificates: tested according to DIN EN 13432
DIN CERTCO certificate No. 7P0305, 7P0306


Customs duty number: 3924.1000
3923.9000

Disclaimer

This confirmation applies to the material supplied by us as described. The material then fulfills the requirements of these guidelines for contact with the specified filling goods, provided the specified food contact conditions are observed. The user must convince himself of the suitability of the material for the intended filling material beyond the requirements of the guidelines.

Reclamation

Deliveries, which differ from the listed specifications, will be withdrawn and replaced after review.

Created by: STOL Date: 08.07.2020	Released by: MEI Andreas Meier (Head of Purchasing)		Version: 5
----------------------------------------------------	----------------------------------------------------------------------	---------------------------------------------------------------------------------------	-------------------



Greenway-Denmark ApS
Administration: Tolnevej 133, Tolne DK-9870 Sindal
Lager: Ole Rømers Vej 1 B DK-9870 Sindal